

LED Downlight Fixture Flood



GENERAL CHARACTERISTICS

Lamp type: LED Downlight Fixture
Bulb: LED Downlight
Base: None
Wattage: 7W (LED)
Voltage: 24VDC
Rated Life: 50,000 hrs
Bulb Material: Aluminum Heat Sink/ PC lens

PHOTOMETRIC CHARACTERISTICS

Initial Lumens: 534 Lm
Mean Lumens: 530 Lm
Initial Lumens per Watt: 76 Lm/Watt
Color Temperature: 2,900K, 3,500K, 4,500K (+/- 50 K)
Color Rendering Index (CRI): 80 Average

DIMENSIONS

Diameter: 4.3 in (110 mm)
Overall Height: 3.8 in (97 mm)

PRODUCT INFORMATION

Product Code: 7D-24V120-YYD
Description: 7W LED Downlight Fixture
Standard Package: Case
Standard Package Quantity: 20*
No Of Items Per Sales Unit: 1
No Of Items Per Standard : 20*
Package

*Product Sold in box of 40

LED Diode Information

Product Code: PL-PT35281
Description: 5050 LED Diode
Input Voltage: 3.1 V
Die: 3 Epistar
Drive Current: 60 mA
Lumens: 20 Lm

60W Halogen Bulbs

0.06kW x 3,000 hours = 180kWh per year
180 kWh x \$0.13 = \$23.40 per year
\$23.40 x 100 bulbs = \$2,340.00 per year

7W LED Downlight

0.007kW x 3,000 hours = 21kWh per year
21 kWh x \$0.13 = \$2.73 per year
\$2.73 x 100 bulbs = \$ 273.00 per year

Product Guantee

The 3 year warranty covers light output over the period and is subject correct storage, installation, operation and maintenance of this product.



WINNER
Best Retro-fit Product

7D-F24V120-YYD

7- 7 Watt
F- Fixture Replacement
24V- 24 VDC Constant Voltage
120- 120 Degree Beam
YY- Kelvin 2700, 3,500K, 4,500K
D- D represent dimmable





www.jirehled.com
info@jirehled.com

MADE IN USA

Photometric Characteristics


Lumens Data

Radiant Flux: 1,466 mW
 Luminous Flux: 543 Lumens
 Luminaire Efficiency: 76 Lumens/Watt
 CCT: 3,347 K
 CRI (Ra): 82.4
 Chromaticity (x): 0.4184
 Chromaticity (y): 0.4055
 Chromaticity (u): 0.2381
 Chromaticity (v): 0.3461
 DUV: 0.0030




LED Depreciation

Jireh Opto LED 5050 SMD Lumen Maintenance
 T_{sp}= 45C T_{air}= 45C I_f= 60mA



Polar Intensity Graph



Product Guarantee

The 3 year warranty covers light output over the period and is subject correct storage, installation, operation and maintenance of this product.



www.jirehled.com
info@jirehled.com

MADE IN USA